

SAFETY DATA SHEET

Page 01 of 03

OSHA's Hazard Communication Standard
29 CFR 1910.1200

Cohesive Solutions Inc.
19215 SE 34 th Street, Ste # 106-390
Camas, WA 98607

SDS # : 075

Phone 1: 1-360 210-7236
Phone 2: 1-800 603-0006 (USA only)

Date: 2/16/2015

SECTION I Product Information

Tradename: (As used on Label) Dermatex
Ingredients: Acrylic Polymer Emulsion

Manufacturers Name : Cohesive Solutions Inc.
Address: 19215 SE 34 th Street # 106 - 390
City: Camas
State and Zip Code : WA 98607

Emergency Phone # : 1-800 603-0006 (USA only)

SECTION II Hazard Identification

This product has been analyzed and shown to not contain any hazardous materials

SECTION III Information on Ingredients

Aromatic / white Acrylic resin suspension (This Product is a Trade Secret)

SECTION IV First Aid Measures

Over Exposure:

Eyes: Can cause irritation, redness, tearing blurred vision
Skin: Prolonged contact may cause slight irritation
Inhalation: Excessive inhalation may cause respiratory irritation
Swallowing: Can cause gastrointestinal irritation, nausea, vomiting, diarrhea

First Aid:

Eyes: Flush with large amounts of water, lifting upper and lower lids, get medical attention
Skin: Wash area with soap and water
Inhalation: If affected, remove individual to fresh air, get medical attention
Swallowing: call Physician

SECTION V Fire and Explosion Hazard Data

Flash Point: 174.9 F , 79.4 C
Autoignition: N/A
Extinguishing Media: For dry polymer use Dry Chemicals, Carbon Dioxide or Water
Special Firefighting Procedure: None required. Product does not burn

Unusual Fire and Explosion Hazards: None

The Product does not burn and is classified Non-Combustible (OSHA/NFPA)

SECTION VI Accidental Release Measures

Provide sufficient ventilation

Spilled polymer emulsion is very slippery. Use care to avoid falls.

Add mix with sand or non-reactive absorbent material and place in an appropriate chemical Waste container

Clean area with water before the material dries

SECTION VII Storage and Handling

Keep container closed and store in dry place above 32 deg. F 0 deg. C , prevent Freezing
Best stored at room temperature

SECTION VIII Exposure / Protective Equipment to be Used

NA

SECTION IX Typical Physical & Chemical Character

Boiling Point: 212 deg F, 100 deg C

Vapor Pressure at 21 C 24.8 hPa

Vapor Density (air = 1) : 1.02g cm³

Flashpoint : 174.9 F / 79.4 C

PH: 4.3

Solubility in Water: 100%

Specific Gravity (H₂O = 1): 1

Evaporation Rate (Butyl Acetate = 1): NA

Appearance and Odor : white liquid/sweet odor

SECTION X Stability and Reactivity Data

Hazardous Polymerization: Cannot occur /Stability: Stable

Hazardous reaction : Vapors may form explosive mixture with air.

Incompatibility: Avoid contact with strong oxidizing agents, strong alkalines, strong acids,

SECTION XI Toxicology

NA

SECTION XII Ecology

NA

SECTION XIII Disposal

Comply with Federal, State and Local Regulation

SECTION XIV Transportation Information

Shipping Name: Resin Compound/not DOT Regulated/keep from freezing
Primary Hazard Class : None
Secondary Hazard Class : None
UN Number : NA
Placard Required : None
Exceptions : N/A

SECTION XV Regulatory Information

Substances on CA Proposition 65 List : none

SECTION XVI Special Precaution or other Comments
--

For external use only. Avoid contact with eyes and mucous membranes.
Keep out of reach of children.
This Product is rated flammable!

COHESIVE SOLUTIONS INC. HAS COMPILED THE INFORMATION AND RECOMMENDATIONS CONTAINED IN THIS MATERIAL SAFETY DATA SHEET FROM SOURCES BELIEVED TO BE RELIABLE AND TO REPRESENT THE MOST REASONABLE CURRENT OPINION ON THE SUBJECT WHEN THIS MSDS WAS PREPARED. NO WARRANTY, GUARANTY OR REPRESENTATION IS MADE AS TO THE CORRECTNESS OR SUFFICIENCY OF THE INFORMATION. THE USER OF THIS PRODUCT MUST DECIDE WHAT SAFETY MEASURES ARE NECESSARY TO SAFELY USE THIS PRODUCT, EITHER ALONE OR IN COMBINATION WITH OTHER PRODUCTS, AND DETERMINE ITS REGULATORY COMPLIANCE OBLIGATIONS UNDER ANY APPLICABLE FEDERAL OR STATE LAW.