

SAFETY DATA SHEET

Page 01 of 03

OSHA's Hazard Communication Standard
29 CFR 1910.1200

Cohesive Solutions Inc.
19215 SE 34 th Street, Ste # 106-390
Camas, WA 98607

SDS # :001

Phone 1: 1-360 210-7236
Phone 2: 1-800 603-0006 (USA only)

Date: 2/1/2016

SECTION I Product Information

Tradename: (As used on Label) MAX Liquid Adhesive
Ingredients: Inert resins/Acetone

Manufacturers Name : Cohesive Solutions Inc.
Address: 19215 SE 34 th Street # 106 - 390
City: Camas
State and Zip Code : WA 98607

Emergency Phone # : 1-800 603-0006 (USA only)

SECTION II Hazard Identification

Ingredients : Inert Resins,

H317: May cause an allergic skin reaction

H319: May cause serious eye irritation

H302: Harmful if swallowed

Ingredients : Acetone,

H225: Highly flammable liquid and Vapor



SECTION III Information on Ingredients

Inert Resins: Appearance and Odor : Transparent amber / aromatic

Solvent: Acetone Volatile (WT.) : Acetone was removed from the list of VOC's effective
September 24.1997 (Federal Register / Vol 62 No 164)

The exact composition has been withheld as Trade Secret

SECTION IV First Aid Measures

Over Exposure:

Eyes: Can cause severe irritation, redness, tearing blurred vision

Skin: Prolonged contact may cause slight irritation and defatting

Inhalation: Excessive inhalation may cause headache, nasal and respiratory irritation

Swallowing: Can cause gastrointestinal irritation, nausea, vomiting, diarrhea

First Aid:

Eyes: Flush with large amounts of water, lifting upper and lower lids, get medical attention

Skin: Wash area with soap and water

Inhalation: If affected, remove individual to fresh air, get medical attention

Swallowing: Give one to two glasses of water and induce vomiting ,call Physician

Carcinogen: None of the substances are listed as a carcinogen by NTP.(National Toxicology Program); or regulated as a carcinogen by OSHA (Occupational Safety & Health Administration).

SECTION V	Fire and Explosion Hazard Data
------------------	---------------------------------------

Flash Point: Closed cup -4.00 deg. F , -20.00 deg C / Open cup NA deg. F , NA deg C .

Autoignition: N/A

Extinguishing Media: Dry Chemicals or Carbon Dioxide

Special Firefighting Procedure: Self contained breathing apparatus with a full facepiece operated in pressure demand or other positive pressure mode.

Unusual Fire and Explosion Hazards: Material is volatile and gives off vapors which may be ignited by open flames, sparks, pilot lights, heaters or smoking.

SECTION VI	Accidental Release Measures
-------------------	------------------------------------

Caution this product is flammable! keep sparks and open flames away

Provide Ventilation, let solvent evaporate, and clean up with paper or other absorbent material, clean area with soap and water.

SECTION VII	Storage and Handling
--------------------	-----------------------------

Keep container closed and store in cool dry place away from heat and open flames, This product is flammable

SECTION VIII	Exposure / Protective Equipment to be Used
---------------------	---

Ventilation : Provide sufficient ventilation

SECTION IX	Typical Physical & Chemical Characteristics
-------------------	--

Boiling Point: 56.11 deg C / 133.00 deg F @ 760 mmHg

Vapor Pressure at 20 C mm Hg: 180

Vapor Density (air = 1) : 2

Volatile (WT.) : Acetone was removed from the list of VOC's effective September 24.1997
(Federal Register / Vol 62 No 164)

Melting Point: N/A

Solubility in Water: Negligible

Specific Gravity (H2O = 1): 0.91

Evaporation Rate (Butyl Acetate = 1): 4.50

Appearance and Odor : Transparent amber / aromatic

SECTION X	Reactivity Data
------------------	------------------------

Hazardous Polymerization: Cannot occur

Stability: Stable

Incompatibility: Avoid contact with strong oxidizing agents, strong alkalines, strong acids,

SECTION XI Toxocoligy

NA

SECTION XII Ecocology

NA

SECTION XIII Disposal

Comply with Federal, State and Local Regulation

SECTION XIV Transportation Information

Shipping Name: Flammable Liquids, n.o.s 3

Primary Hazard Class : Flammable

Secondary Hazard Class : none

UN Number : UN1993 UN Pack Group : II

Placard Required :Flammable

Exceptions : CFR 49 Section 173.150 allows Ground Shipping as "Limited Quantities"

Consult CFR 49 and your shipper for more detailed information

SECTION XV Regulatory Information

Substances on CA Proposition 65 List : none

SECTION XVI Special Precaution or other Comments

For external use only. Avoid contact with eyes and mucous membranes.

Keep out of reach of children.

This Product is rated flammable!

COHESIVE SOLUTIONS INC. HAS COMPILED THE INFORMATION AND RECOMMENDATIONS CONTAINED IN THIS MATERIAL SAFETY DATA SHEET FROM SOURCES BELIEVED TO BE RELIABLE AND TO REPRESENT THE MOST REASONABLE CURRENT OPINION ON THE SUBJECT WHEN THIS MSDS WAS PREPARED. NO WARRANTY, GUARANTY OR REPRESENTATION IS MADE AS TO THE CORRECTNESS OR SUFFICIENCY OF THE INFORMATION. THE USER OF THIS PRODUCT MUST DECIDE WHAT SAFETY MEASURES ARE NECESSARY TO SAFELY USE THIS PRODUCT, EITHER ALONE OR IN COMBINATION WITH OTHER PRODUCTS, AND DETERMINE ITS REGULATORY COMPLIANCE OBLIGATIONS UNDER ANY APPLICABLE FEDERAL OR STATE LAW.